

June, 2020

3M™ High Performance Green Masking Tape 401+

Product Description

3M[™] High Performance Green Masking Tape 401+ is a green colored crepe paper masking tape for critical paint masking applications in the automotive, specialty vehicle, and industrial markets where excellent holding and high temperature performance (up to 250°F [121°C]) are required.

Product Features

- Creates sharp paint lines and resists edge bleed by most industrial paints.
- Removes cleanly. Adhesive and backing resist leaving residue and slivering.
- Conforms around curves and contours. Crepe paper backing is highly conformable.
- Sticks with confidence to most surfaces including metal, glass, plastic, rubber, and paint. Adhesive is 3M proprietary solvent-free.
- Highly visible green color aids accurate masking.
- Prolonged outdoor exposure may make tape difficult to remove.



3M™ High Performance Green Masking Tape 401+

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Method
Color	Green		
Total Tape Thickness	0.16 mm	6.4 mil	ASTM D3652
Backing	Smooth crepe paper treated with a heat resistant saturant		
Adhesive	Natural / Synthetic Rubber Blend		

Typical Performance Characteristics

Property	Values		Method	Notes
180° Peel Adhesion	3.8 N/cm	35 oz/in	ASTM D3330	12 in/min (300 mm/min) Initial Dwell, Stainless Steel
Tensile Strength	42 N/cm	24 lb/in	ASTM D3759	
Elongation at Break	14 %		ASTM D3759	
Temperature Use Range	30 minutes up to 121 °C	30 minutes up to 250 °F		

Available Sizes

Property	Values		Notes
Standard Roll Length	55 m	60 yd	Available in metric widths (eg, 24 mm corresponds to 1 inch).

Storage and Shelf Life

Store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton. To obtain best performance, use within 12 months from date of manufacture.

Trademarks

3M is a trademark of 3M Company.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/company-us/all- 3m-products/~/3M-High-Performance-Green- Masking-Tape-401?N=5002385+3293193657&rt=rud
Safety Data Sheet (SDS)	https://www.3m.com/3M/en_US/company-us/SDS-search/results/? gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=401

ISO Statement

This Closure and Masking Systems Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ High Performance Green Masking Tape 401+

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.



